

## M A T E R I A L   S A F E T Y   D A T A   S H E E T

PRODUCT NAME: CLEAR ACR.W/PROOF'G CONC. & MASONRY SEALER  
 PRODUCT CODE: 47-423

HMIS CODES: H F R P  
 2\*1 0

## ===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: NELSONITE POOL AND DECK COATING  
 ADDRESS : 3150 E. PICO BLVD.

LOS ANGELES, CA 90023-3683

EMERGENCY PHONE(CHEMTREC) : (800) 424-9300      DATE PRINTED : 10/23/06  
 INFORMATION PHONE : (800) 544-1998      NAME OF PREPARER : N/A

## ===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mmHG	@TEMP(F)	WEIGHT PERCENT
~ DIETHYLENE GLYCOL MONOMETHYL ETHER OSHA PEL: N/E, ACGIH TLV: N/E	111-77-3	.1	68	2.81
BUTYL BENZYL PHTHALATE	85-68-7	.16	302	1.6
~ AMMONIUM HYDROXIDE ACGIH TLV: 25 ppm	1336-21-6	420	60	0.62

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

## ===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): 195 - 450      DENSITY: 9.14 lb/gl  
 VAPOR DENSITY: HEAVIER THAN AIR      SPECIFIC GRAVITY (H2O=1): 1.10  
 COATING V.O.C.: 1.91 lb/gl      MATERIAL V.O.C.: 0.69 lb/gl  
 COATING V.O.C.: 229 g/l      MATERIAL V.O.C.: 83 g/l  
 SOLUBILITY IN WATER: Partial      EVAPORATION RATE: SLOWER THAN ETHER  
 APPEARANCE AND ODOR: Clear liquid with slight vinegar odor.

## ===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (Deg F): >200      METHOD USED: TCC  
 FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: .26      UPPER: n/a

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

## SPECIAL FIREFIGHTING PROCEDURES

Wear self-contained breathing equipment in confined areas to avoid inhalation of smoke or fumes. Water should be used to keep fire-exposed containers cool.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, sparks, electrical equipment and open flames. Vapors formed by this product may travel and be ignited by sources distant from the handling or use point.

## ===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

## CONDITIONS TO AVOID

Sparks, flames, excessive heat, poor ventilation.

## INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents

## HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

## HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

## ===== SECTION VI - HEALTH HAZARD DATA =====

## INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Its use in poorly ventilated areas can cause nausea, headache and dizziness.

## SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Short-term contact will result in eye irritation. Prolonged and repeated contact can cause a drying of the skin and irritation.

## SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause skin irritation.

## INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Adverse health effects from ingestion may include respiratory irritation, nausea and vomiting. Not expected to be acutely toxic by ingestion.

## HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause eye and skin irritation, nausea, headache and dizziness.

Chronic: Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED: Yes

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

## EMERGENCY AND FIRST AID PROCEDURES

INHALATION: MOVE PERSON TO FRESH AIR. PROVIDE ARTIFICIAL RESPIRATION OR OXYGEN IF BREATHING IS DIFFICULT. EYE & SKIN CONTACT: FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. WASH AFFECTED AREAS WITH SOAP AND WATER IMMEDIATELY. REMOVE CONTAMINATED CLOTHING. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION. ABSORB WITH INERT MATERIAL (SAND, VERMICULITE, ETC.), SWEEP OR SCOOP UP AND PUT IN DISPOSAL CONTAINER. FLUSH AREA OF SPILL WITH WATER.

## WASTE DISPOSAL METHOD

Incinerate or dispose of in accordance with local, state and federal regulations.

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

COMBUSTIBLE! Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep away from children.

## OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact with skin.

## ===== SECTION VIII - CONTROL MEASURES =====

## VENTILATION

Local exhaust at point of use in closed spaces.

RESPIRATORY PROTECTION

Use self-contained breathing apparatus where vapor concentration may be above TLV limits. Where vapor does not exceed TLV limits, use NIOSH approved respirator.

PROTECTIVE GLOVES

Chemical resistant gloves

EYE PROTECTION

Safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye bath and safety shower

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Contains: Butyl Benzyl Phthalate(BBP) -

===== SECTION X - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, NELSONITE POOL AND DECK COATING makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. NELSONITE POOL AND DECK COATING assumes no responsibility for injury from the use of the product described herein.