

# MATERIAL SAFETY DATA SHEET

## PRODUCT IDENTIFICATION

TRADE NAME TOTAL BOND	GENERIC NAME NON RE-EMULSIFIABLE BONDING AGENT		
MANUFACTURER'S NAME FLORIDA STUCCO CORP.	CAS NUMBER N/A		
ADDRESS (STREET) 21195 BOCA RIO ROAD	PHONE NUMBER (EMERGENCY) (561) 487-1302		
CITY BOCA RATON	STATE FLORIDA	ZIP 33433	CHEMICAL STRUCTURE N/A

## I • PRODUCT INGREDIENTS

CHEMICAL AND/OR COMMON NAME	CAS NUMBER	TLV/PEL

## II • PHYSICAL DATA

BOILING POINT >212.00F >100.00C	VAPOR PRESSURE	SPECIFIC GRAVITY 1.07	MELTING POINT No Data
SOLUBILITY IN WATER	VAPOR DENSITY (AIR = 1) of water vapor	PERCENT VOLATILE	EVAPORATION RATE
APPEARANCE AND ODOR White liquid sweet			

## III • FIRE AND EXPLOSION DATA

FLASH POINT No Data	FLAMMABLE LIMITS 0	FLAMMABLE LIMITS	LEL	UEL
EXTINGUISHING MEDIA				
SPECIAL FIREFIGHTING PROCEDURES				
UNUSUAL FIRE OR EXPLOSION HAZARDS				

## IV • HEALTH HAZARD INFORMATION

### HAZARD BY ROUTES OF EXPOSURE

INHALATION

EYE

Rinse immediately with plenty of water.

SKIN CONTACT/ABSORPTION

Wash affected area with soap and water.

SIGNS AND SYMPTOMS ASSOCIATED WITH EXPOSURE OVER TLV

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED

None known

ANY OF PART I LISTED AS CARCINOGENS? (NTP, IARC, OSHA)

Vinyl acetate monomer (IARC)

HEALTH HAZARD INFORMATION CONTINUED ON BACK

## V • HEALTH HAZARD INFORMATION (Continued)

### EMERGENCY/FIRST AID PROCEDURES

#### INHALATION

Remove to fresh air — contact a physician.

#### INGESTION

Drink 2 glasses of milk or water followed by fruit juices or diluted vinegar to neutralize the alkali; then contact a physician. May cause cancer.

#### EYE CONTACT

Irrigate eyes with plenty of water for at least 15 minutes — contact a physician.

#### SKIN CONTACT

Wash affected areas of the body with soap and water.

#### SKIN CONTACT (acute)

Wet cement based materials can dry the skin and cause alkali burns — wash affected areas with soap and water.

## VI • CONDITIONS FOR SAFE USE (When over TLV)

#### RESPIRATORY PROTECTION

NIOSH/MSHA approved respirator designated for nuisance dust.

#### EYE PROTECTION

Chemical safety glasses.

#### PROTECTIVE GLOVES

Rubber gloves.

#### OTHER PROTECTIVE CLOTHING/EQUIPMENT

Protect skin from exposure. Plastic cement burns with little warning; minor heating sensation is noticed.

#### VENTILATION REQUIREMENTS

Recommended to keep dust below TLV level.

## VII • REACTIVITY DATA

IS MATERIAL STABLE?

WILL HAZARDOUS POLYMERIZATION OCCUR?

INCOMPATIBILITY

Reactive metals

CONDITIONS TO AVOID

HAZARDOUS DECOMPOSITION PRODUCTS

## VIII • SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED

Inert dry powder — may be swept or shovelled; dispose of in accordance with local, state and federal regulations.

Avoid breathing dust.

WASTE DISPOSAL METHOD

Normal methods of disposal for non-reactive minerals; dispose of in accordance with state, local & federal regulations.

RCRA REGULATED

Yes  No

RCRA NUMBER

CERCLA (Superfund) REPORTABLE QUANTITY

DOT REGULATED

Yes  No

DOT PROPER SHIPPING NAME

DOT HAZARD CLASS

DOT NUMBER

## IX • SPECIAL PRECAUTIONS

SPECIAL PRECAUTIONS FOR HANDLING AND STORAGE

OTHER PRECAUTIONS

PREPARED BY

FLORIDA STUCCO CORP.

PHONE NO.

(561) 487-1302

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, THE MANUFACTURER MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.